


# SERIES 34 ALUMINIUM TRUCK SHUTTERS

"ROBINSON" SHUTTERS ENGINEERED IN SEARCH OF EXCELLENCE



34 mm hollow slats create a superior heavy duty shutter which is exceptionally easy to operate and the most advanced of designs.

## RECOMMENDED SPECIFICATIONS

Series 34 Aluminium Truck Shutter, as manufactured by Mirage Industries Pty, Ltd., Australia. Product Code AE/ROB/34.

## APPLICATIONS

Specified Australia-wide for State Emergency Service Vehicles, Fire Fighting Vehicles, and other applications where strength and weather resistance is required. Top, Bottom, Side seals and unique lift bar bottom rail are usually standard requirements.

## FINISH

Available in matt natural, anodised and a range of powdercoated colours.

## SIZES

A single door is available to suit an opening up to 2.0 metres high by 1.9 metres wide.

## STANDARD CURTAIN

Made of double skin aluminium extruded slats. Each slat has a flat face of 34mm and each skin is 1.2mm thick. In between each slat is a nylon/P.V.C. co-extrusion which is inserted so as to create a weather seal and to eliminate rattling. Both ends of every aluminium slat are fitted with a solid interlocking nylon clip that secures slats laterally and takes up wear. When assembled these slats create a modern flat surface perfect for sign writing.

Call 1800 465 599 or visit [www.miragedoors.com.au](http://www.miragedoors.com.au)

 **MIRAGE**  
DOORS

## BRACKET OPTIONS

All bracket styles have the channel guide pre-fixed for smooth operation and ease of installation.

**Fixed Position Front Roll Bracket** - The most basic and simple design. The top slat is bolted directly to the drum.

**Pennant Plate Front Roll Bracket** - The drum slides in the bracket to provide minimum clearance from the header plate at all times. The top slat is bolted directly to the drum.

**Minimum Radius Front Roll Bracket** - Designed to take up the minimum amount of headroom. The top slat of the curtain is connected to the drum via cables.

**Roof and Rear Roll Bracket** - The drum is mounted in a fixed position to the rear of the roof cavity. The top slat of the curtain is connected to the drum via cables.

Maximum Shutter size using this type of Bracket would be 1600mm wide x 1900mm high

**Roof Cable Front Roll Bracket** - The drum is mounted in a fixed position. Bottom rail of the curtain is connected to the drum via cables.

Maximum Shutter size using this type of Bracket would be 1600mm wide x 1900mm high

## CHANNEL GUIDES

1.6mm thick folded Zinalume® (22mm deep x 23mm wide).

## ROLLER DRUM

The drum is manufactured from 100mm diameter extruded aluminium tube, solid nylon end caps and a solid steel shaft. Helical oil tempered springs are completely concealed and supplied pre-tensioned for fast installation.

## BOTTOM RAIL

The bottom rail is extruded aluminium section fitted with a rear aluminium cover plate designed to cover the locking device. It comes standard with heavy duty finger pull extrusion, nylon end shoes and rubber seal. Stop brackets bolted to the inside of the bottom rail eliminate damage to header plate.

## LOCKING OPTIONS


- Flush Fitting Key Lock
- "T" Handle - Key locking or non-locking.
- Lift Bar Rail - Incorporating flush key locking or non-locking.
- Sliding Shoot Bolts

## SEAL OPTIONS

**Small Top Seal** - Anodised aluminium extrusion incorporating 113mm brush.

**Heavy Duty Top Seal** - Anodised aluminium "J" gutter extrusion incorporating brush seal in 30mm.

**Side Seal** - Aluminium extrusion incorporating rubber side seal.



Mirage has a continuous program of product development and reserves the right to change specifications at any time without notice.

Call 1800 465 599 or visit [www.miragedoors.com.au](http://www.miragedoors.com.au)

 **MIRAGE**  
DOORS