



**Durulite STANDARD Traffic Doors
Single Panel
(All use except Forklift)**

Fully Gasketed MODEL#	FINISHED OPENING REQUIRED	
	"W" Door Width Size	"H" Door Height Size
	i.e. Daylight width between steel jambs	i.e. Daylight between finished floor and underside between finished of the head of Steel Jambs
2478 FS	610	1980
2484 FS	610	2135
2490 FS	610	2285
2496 FS	610	2440
2778 FS	685	1980
2784 FS	685	2135
2790 FS	685	2285
2796 FS	685	2440
3078 FS	760	1980
3084 FS	760	2135
3090 FS	760	2285
3096 FS	760	2440
3278 FS	815	1980
3284 FS	815	2135
3290 FS	815	2285
3296 FS	815	2440
3478 FS	865	1980
3484 FS	865	2135
3490 FS	865	2285
3496 FS	865	2440
3678 FS	915	1980
3680 FS	915	2035
3684 FS	915	2135
3690 FS	915	2285
3696 FS	915	2440
3978 FS	1005	1980
3984 FS	1005	2135
3990 FS	1005	2285
3996 FS	1005	2440
4278 FS	1070	1980
4284 FS	1070	2135
4290 FS	1070	2285
4296 FS	1070	2440
4884 FS	1220	2135
4890 FS	1220	2285
4896 FS	1220	2440

**F.S. = FULLY GASKETED; SINGLE PANEL
FOR SIZES NOT LISTED, PLEASE CONSULT FACTORY**

Mirage Doors has a continuous program of product development and reserves the right to change specifications at any time without notice.

- PLEASE NOTE
1. IF INADEQUATE ACCESS IS PROVIDED MIRAGE WILL NOT BE HELD RESPONSIBLE FOR MAINTENANCE NOR THE COSTS INCURRED TO CREATE ADEQUATE ACCESS
 2. ALL STRUCTURAL SUPPORTS FOR BRACKETS AND SIDE GUIDES TO BE PROVIDED BY OTHERS