

## PRODUCT SPECIFICATION – ‘SD100 FOLDING CLOSURE’

### PROPRIETARY SPECIFICATION

SD100 folding closure as manufactured by Mirage Doors

#### PANEL OPTIONS

Aluminium framing, fitted with 3mm polycarbonate.

#### TOP TRACK

Extruded aluminium overhead track 35mm wide x 41mm high.

#### OPERATION

Manual by hand

#### LOCKING

Lockwood two way cylinder security lock supplied as standard (master keying by others)

Floor mounted sockets / ferrules will be provided, to ensure the concealed drop bolts engage into the floor.

#### FINISH OPTIONS

- Etch & clear anodised (standard);
- Dulux Duralloy or Interpon D1000 powdercoat finishes are suitable for the SD Folding Closure range.

#### SPECIAL NOTES

- Preparation of openings to suit the folding closures is by others;
- The head support must be structural to support a product weighing 14kgm<sup>2</sup>. As the panels when opened will carry the full weight of the closure, supports to carry the full weight of the closure will be required;
- Floors and overhead track supports must be true & level;
- Work by others:
  - Stacking boxes or joinery for storage of opened panels;
  - Structurally adequate wall / mounting points to support the folding closure;
  - Adequate clearances & supports as per Tech. Data sheets to ensure successful operation;
- Product & installation warranty – 12 months.

Mirage Doors has a continuous program of product development, and reserves the right to change specifications at any time without notice.