

PRODUCT SPECIFICATION – ‘SD200 FOLDING CLOSURE’

PROPRIETARY SPECIFICATION

SD200 folding closure as manufactured by Mirage Doors

PANEL OPTIONS

Aluminium framing, fitted with 3mm clear toughened glass or 3mm solid aluminium sheet.

TOP TRACK

Extruded aluminium overhead track 35mm wide x 41mm high.

OPERATION

Manual by hand

LOCKING

Lockwood two way cylinder security lock supplied as standard (master keying by others)

Floor mounted sockets / ferrules will be provided, to ensure the concealed drop bolts engage into the floor.

FINISH OPTIONS

- Etch & clear anodised (standard);
- Dulux Duralloy or Interpon D1000 powdercoat finishes are suitable for the SD Folding Closure range.

SPECIAL NOTES

- Preparation of openings to suit the folding closures is by others;
- The head support must be structural to support a product weighing 14kgm². As the panels when opened will carry the full weight of the closure, supports to carry the full weight of the closure will be required;
- Floors and overhead track supports must be true & level;
- Work by others:
 - Stacking boxes or joinery for storage of opened panels;
 - Structurally adequate wall / mounting points to support the folding closure;
 - Adequate clearances & supports as per Tech. Data sheets to ensure successful operation;
- Product & installation warranty – 12 months.

Mirage Doors has a continuous program of product development, and reserves the right to change specifications at any time without notice.