

WEATHERTITE

DESIGNED TO BE THE ULTIMATE IN LONGEVITY AND VALUE.



INTRODUCING THE WEATHERTITE DOOR

Get more long-term value from your trucks and trailers with TODDCO's WeatherTite roll-up door. Crafted from tough polycomposite material, it eliminates worries about the biggest threat to door durability: water penetration. Because it's completely resistant to moisture, the WeatherTite door prevents swelling, warping, finish problems, delamination, and rotting. It's also built to withstand the day-to-day challenges every fleet faces, providing dependable performance in all conditions. Learn the key facts about this proven TODDCO innovation and see why it has been a trusted choice for years. Then bring on the rainiest days. Now with the WeatherTite door, it's great weather for TODDCO.

WEATHERTITE PANEL 12-MONTH LIMITED WARRANTY.

TODCO warrants to the original end-user purchaser of the WeatherTite door that the door panels will be free from defects in material and workmanship for a period of twelve (12) months from the date of delivery, subject to all terms, conditions and limitations.

Equipment Specification:

Designed to be the Ultimate in LONGEVITY AND VALUE.

The WeatherTite panel is made from a recyclable polycomposite, that is extruded all in one piece. The extrusion process creates extra thick walls, the internal rib and the patented joint system, that sheds water even when the door is being opened. This makes these panels very durable and tough enough to compete with the plywood cored dry freight doors while being impervious to moisture.

**WEATHERTITE
DOORS DROP INTO ALL
EXISTING 3/4" TRACK
CONFIGURATIONS.**



Adjustable top fixtures plus rubber head seal provide tight seal at top of door.



Aluminium reinforcement straps required for door openings in excess of 87" wide.

Tough double-wall panels
Are extruded in one piece for added strength.


Three rows of center hinges
Standard on panels 73" or wider.

No thru rivets on center hinges.
Gives the door a smooth surface for an automotive quality paint finish and/or excellent decal adhesion.

Standard bottom seal for weather protection.

Unique joint configuration

Forces water flow downward, while keeping door panels properly aligned and rigid.



Panel configuration
Accepts TODDCO standard hardware.

Horizontal reinforcement ribs add to the strength.

Polycomposite construction makes the door impervious to moisture.
Smooth, high quality finish makes painting optional.

Strong four-knuckle end hinges.

Unique panel joints designed to form a better water barrier. Also designed for maximum pinch protection.



Side seals standard.